



Compatibility



## Description

The RY-AirForce II inflator gun complies with Order ICT/155/2020 regulating metrological control.

Its **robust** and **lightweight** design has been further enhanced with a **nylon body** and a **new metal inlet**, making it ideal for any type of environment.

With a **user-friendly display** for quick and trouble-free inflation, this **pressure gauge** has **BS EN 12645:2014** approvals and certifications.

It features a **high performance mechanical dial** with approvals to meet the latest industry standard **EC86/217**.



## Technical Data and Dimensions

<b>Dimensions</b>	250 x 110 mm
<b>Weight</b>	350 g
<b>Operation temperature</b>	-20 / +60 °C
<b>Humidity range</b>	up to 95 % RH w/o condensation
<b>Reading accuracy</b>	0.1 bar / 2 psi / 10 kPa
<b>Max inlet pressure</b>	15 bar / 218 psi / 1,500 kPa
<b>Inflation range</b>	0 - 12 bar / 170 psi / 1,200 kPa
<b>Inflation flow</b>	Max. 910 l/min @ 13 bar supply

## Standard Equipment

- ✔ Tire inflating gun with pressure gauge

## Features

- ✔ Modern design
- ✔ Lighter design
- ✔ Shock resistant design
- ✔ New nylon handle function
- ✔ Metallic inlet as standard
- ✔ Proven Bourdon tube with beryllium construction for robustness
- ✔ Direct valve design increasing inflation and deflation rates
- ✔ Built in swivel and hanging device
- ✔ Scales: bar, psi and kPa