



TIRE INFLATING GUN

RY-AIRFORCE II

The new RY-AirForce II inflator gun complies with Order ICT/155/2020 regulating metrological control.

Its robust and lightweight design has been further enhanced with a nylon body and a new metal inlet, making it ideal for any type of environment.

With a user-friendly display for quick and trouble-free inflation, this pressure gauge has BS EN 12645:2014 approvals and certifications.

It features a high performance mechanical dial with approvals to meet the latest industry standard EC86/217.



Standard Equipment:

- ✔ Tire inflating gun with pressure gauge

Main features:

- ✔ Modern design
- ✔ Lighter design
- ✔ Shock resistant design
- ✔ New nylon handle function
- ✔ Metal inlet as standard
- ✔ Proven Bourdon Tube with beryllium copper construction for robustness
- ✔ Direct valve design increasing inflation and deflation rates
- ✔ Built in swivel and hanging device
- ✔ Scales: bar, psi y kPa

Technical data:

Dimensions	250 x 110 mm.
Weight	350 gr.
Operating Temperature range	-20°C - 60°C
Humidity range:	Up to 95 % RH non-condensing
Reading Accuracy:	0.1 bar / 2 psi / 10 kPa
Max Inlet Pressure	15 bar/ 218 psi/ 1500 kPa
Inflation Range	0-12 bar/ 170 psi/ 1200 kPa
Inflation flow	Max. 910 l/min @ 13 bar supply